




10/530362
PCT/GB 2003 / 004437
Rec'd CT/PTO 04 APR 2005



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

BEST AVAILABLE COPY

Signed *AmBrewster*

Dated 12 November 2003

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The
Patent
Office

07OCT02 E733433-1/000180
P01/7700 0.00-0223064.7

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference

ABC/21078

2. Patent application number

(The Patent Office will fill in this part)

0223064.7

04 OCT 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

PBT (IP) Limited

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

1 Astra Centre
Edinburgh Way
Harlow
Essex
CM20 2BN
United Kingdom

4. Title of the invention

GAS VALVE WITH PROPORTIONAL
OUTPUT

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom
to which all correspondence should be sent
(including the postcode)

A A Thornton & Co
235 High Holborn
London
WC1V 7LE

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 8

Claim(s)

Abstract

Drawing(s) 2 + 2

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)


Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature



Date

4 October 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

Andrew B Crawford - 020 7405 4044

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) *If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- b) *Write your answers in capital letters using black ink or you may type them.*
- c) *If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- d) *If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- e) *Once you have filled in the form you must remember to sign and date it.*
- f) *For details of the fee and ways to pay please contact the Patent Office.*

GAS VALVE WITH PROPORTIONAL OUTPUT

The present invention relates to the control of low pressure combustible gas flow.

5 Indexing mechanisms that amplify piezo electric actuator motion, as disclosed in UK Patent Application GB0030263.8 and GB0011350.3 can be used to provide gradual opening of a face seal, but the cost of such systems is prohibitive when compared to a manual solution.

10 Poppet valves, where the seal is pressed onto an orifice and lifted off are commonly used in such applications, but proportional control of such devices is hampered by the nature of their opening. In a situation where the incoming gas pressure is resisted by a spring and the actuator pulls the spring off, the forces required are increased for the actuator by the spring's sealing force and additionally by its spring rate. When the valve is closed by the gas pressure the
15 pressure differential collapses as the seal begins to open, and the actuator then overshoots. Solutions such as motors with worm drives can solve this problem, but at a cost that is prohibitive.

For cost reasons it is desirable to make use of simple parts with low energy consumption and this has caused piezo-electric actuators to be considered.
20 However, such actuators encounter problems where the movement required is large. When dealing with gas valves, the movement is determined by the diameter of the inlet orifice. Smooth flow is obtained only when the seal is a minimum of 25% of the diameter above the orifice, as shown in Figure 1. This is because the area of a cylinder Diameter D and 25% of D high is equivalent to the area of the
25 hole D, so the opening does not constitute a restriction.

Gas control valves are required to have a pressure drop of around military when passing their maximum flow rate, although this varies slightly with different

specifications. In order to achieve such a low pressure drop it is necessary for the orifice to be roughly the same size as the incoming pipe. In most cooker installations the pipe has an internal diameter of 4mm, so the valve must lift at least 1 mm clear of the orifice, and preferably more. This amount of movement
5 can only be achieved from a piezo-ceramic bender, not a stack, but only a limited range of designs offer such a movement at a reasonable cost.

Another factor is that the force available from a piezo-electric bender reduces linearly with the displacement, as shown in Figure 2. In order to maintain a useable level of force the assembly must work within 50% of the force and 50%
10 of the unloaded deflection, as shown by the shaded box of Figure 2.

From the above information it can be seen that working with a bottom pressure system is unattractive, because the closure spring will double the work needed from the actuator, thus reducing by half the movement which is already close to the practical limits. Achieving the level of movement from the bender
15 will require a system of relatively low stiffness. If the system is of low stiffness the process of opening against the gas pressure must resist the impulse caused by the collapse as the valve opens. If the actuator is flexible enough to give the motion required it tends to pull off the orifice and enter into a non-controlled oscillation that makes it impossible to accurately regulate the gas flow.

20 It is desirable to have a means of opening top pressure valves that prevents the unregulated oscillation whilst also permitting the full range of actuator motion to be used.

The present invention provides a valve for controlling fluid flow comprising a body provided with a fluid passageway having an inlet and an outlet,
25 a valve member for inhibiting fluid flow through the passageway, and means for moving the valve member so as to provide for controlled flow of fluid from the

inlet to the outlet, wherein the valve member is in the form of a blade which is pivotable about an axis remote from the passageway.

Preferably, the blade is formed to provide the desired force/displacement characteristics.

5 In a preferred embodiment, the means for moving the valve member is a piezo-electric actuator. Also, the valve may be provided with a plurality of inputs each provided with its own valve member. The characteristics of the valve members need not be the same in this case, but preferably a single actuator is used to operate the two valve members.

10 Further, a plurality of valves can be located side by side in a valve assembly which permits the assembly to be constructed from a number of layers.

In order that the present invention be more readily understood, an embodiment will now be described by way of example with reference to the accompanying drawings, in which:-

15 Fig 1 shows a diagram to explain the basic principles behind the present invention;

Fig 2 shows a further diagram to explain the basic principles behind the present invention;

20 Figs 3a to 3c show plan views of three different shapes of valve member useful with the present invention;

Fig 4 shows a diagrammatic side view of a part of a valve according to an embodiment of the present invention;

Fig 5 shows a modification of a part of the valve shown in Fig 4;

25 Fig 6 shows a top plan view of an array of valve members which can be used with the present invention; and

Fig 7 shows a perspective view of a complete valve assembly of a plurality of valves, each as represented by Fig 4.

According to the present invention there is provided a sealing system comprising an orifice and a valve member in the form of a thin blade of suitable dimensions and finish to form a gas-tight seal when top pressure of 20mBar is applied. The blade is preferably of metal. A number of blade shapes are suited to this application. A simple cantilever, a constant stress beam or a convolute that changes its stiffness geometrically as it opens are examples of such a blade. These fundamental beam shapes are shown in Figure 3 by way of illustration only.

The shapes of Figure 3 can be modified to have increasing or decreasing stiffness by the introduction of cutouts and other features.

Consider now the circumstance of the valve in the closed state, as shown in Figure 4, being a section through the valve, with no top. The arrows (20) signify the gas pressure. There is provided a bypass blade (40), a main flow blade (50) and a lifting member (60). The blades are located on the top surface (101) of the valve body (100) and the rear edges (41,51) are fixed to the body in some convenient manner eg by clamping, welding or bonding. The lifting member (60) is connected to a suitable piezo-electric actuator, but can equally well be connected to a magneto-strictive, electro-strictive or other active material than can be formed into a bender configuration. For low speed operation the mechanism may also be operated by a thermal bimetal.

The bypass blade (40) covers a bypass channel (70) that permits a restricted amount of gas to flow to the outlet of the valve (90), giving a controlled low-level flame suitable for pilot lights and simmer functions. The main flow blade (50) covers a main channel (80) that provides the full flow characteristic of the valve.

The force required to lift the blade from the sealed condition is defined by the equation:

$$F=S_1+(S_xd)+(P_xA)$$

Where

S1 is the initial compression applied by the seal blade;

5 S is the spring rate of the seal blade;

d is the distance needed to overcome any compliance in the seal;

P is the gas pressure difference between the valve and the outlet;

A is the area of the orifice being opened.

10 The same equation applies throughout the opening action. The valve lifter (60) has two steps on it such that the pilot port is opened first. The valve blades are made from thin material, typically 50 micron thick stainless steel, so the initial pre-load is in the order of 0.02N. The pressure exerted by the gas at 50mB operating temperature ($P \times A$) is about 0.01N, and the distance to open is around 20
15 microns. Such a system requires just 0.05N to open it, and after the initial seal is broken the later seal is working with pressure differentials of just 10-15mBar, making it easier still to open.

The bypass blade (40) covers a bypass channel (70) that permits a restricted amount of gas to flow to the outlet of the valve (90), giving a controlled low-level
20 flame suitable for pilot lights and simmer functions. The main flow blade (50) covers a main channel (80) that provides the full flow characteristic of the valve.

The force required to lift the blade from the sealed condition is defined by the equation:

25 $F = S1 + (S \times d) + (P \times A)$

Where

- S₁ is the initial compression applied by the seal blade;
 S is the spring rate of the seal blade;
 d is the distance needed to overcome any compliance in the seal;
 5 P is the gas pressure difference between the valve and the outlet;
 A is the area of the orifice being opened.

The same equation applies throughout the opening action. The valve lifter (60) has two steps on it such that the pilot port is opened first. The valve blades
 10 are made from thin material, typically 50 micron thick stainless steel, so the initial pre-load is in the order of 0.02N. The pressure exerted by the gas at 50mB operating temperature (PxA) is about 0.01N, and the distance to open is around 20 microns. Such a system requires just 0.05N to open it, and after the initial seal is broken the later seal is working with pressure differentials of just 10-15mBar,
 15 making it easier still to open.

The phenomenon of uncontrolled oscillation is reduced by having sufficient stiffness in a simple cantilever, but preferably the blade is of such a form as to rapidly increase in stiffness as the orifice is opened. The deflection of a beam is determined by the equation:

20

$$d = wl^3/3EI$$

- Where d is the deflection
 W is the load
 25 I is the length of the cantilever
 E is the Young's Modulus of the material
 I is the second moment of inertial of the section

For a simple beam the second moment of inertia is defined by

$$I=bd^3/12$$

5

Where b is the width
d is the beam thickness

If the width of the beam changes as a geometric progression the relative
10 deflection will change as a linear inverse of this value. In the concept shown in
Figure 3c of the part becomes increasingly stiff to move. In Figure 5 the position
of the orifice (80) is shown relative to the beam shape. When the operating
pressure drop is higher it may be desirable to increase the rate of stiffness change,
and to do this the value d can be changed, because this is a cubic function. This is
15 achieved by the introduction of an auxiliary blade (55) that is shown in Figure 5.
The orifice is firstly uncovered by the flexible blade and, as the pressure
differential collapses, the oscillation is damped by the stiffer component.

The nature of the valve function is conveniently suited to the fabrication of
the components in layers, permitting the replication of the basic construction as a
20 multiple-output system. Figure 6 shows an array of 7 valve blades formed from a
single sheet of material. The array can be any suitable multiple, seven being
sufficient for four hobs, a grill and two ovens.

The use of a piezo electric bender actuator permits the actuators to be made
as a single part or, if preferred, a multiplicity of single acting devices. Figure 7
25 shows a complete valve assembly having its actuators formed as a single array.

Through the above and similar constructions can be achieved a proportional
electronic valve that uses low-force, high movement actuators to work against a

top pressure in the region 20-200mBar with the control of the critical opening and restriction zones to prevent sudden opening and thus uncontrolled fluctuation in flow.

1/2




FIG. 1







FIG. 2



a) Cantilever



b) Constant Stress



c) Geometric Progression

Figure 3




Figure 4

2/2




FIG. 5




Figure 6




FIG. 7

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.